

◎ HOLE IN CHASSIS:





◎ MAXIMUM THICKNESS: 1.2 mm

◎HF

◎ROHS compliant

DRAW NO. PGAS016973

GJS

|   |   |                  |  |  |  |  |
|---|---|------------------|--|--|--|--|
| <b>PLASTIC TOLERANCE:</b><br>L≤10 ±0.2<br>10<L≤30 ±0.3<br>30<L≤50 ±0.5<br>50<L≤100 ±0.7<br>100<L≤250 ±1.2<br>ABOVE 250 ±1.5 | 網頁圖示供參考,最終以品固公司正式圖面為主<br>The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD. |                  |  品固企業股份有限公司<br>品基電子(東莞)有限公司<br>蘇州品基電子科技有限公司<br>鑽隆有限公司<br>PINGOOD ENTERPRISE CO.,LTD. | <b>PART NAME:</b><br>印刷電路板導槽<br>PCB GUIDE RAIL |  |  <b>VERSION</b><br>4A |
|   | <b>MATERIAL:</b> N66 V2 or EQUIVALENT<br><b>COLOR:</b> NATURAL  |                  |  | <b>PART NO:</b><br>CG-2AX4                     |  |  |
|    | <b>UNIT</b><br>mm   | <b>SCALE</b><br> |  |  |  |  |

表單號碼QF135