



◎ CHASSIS THICKNESS: 0.8 mm

◎ HOLE IN CHASSIS: $\phi 6.4$

1.符合歐盟規範

◎ 鎘 (Cd) <100ppm

◎ 鉛 (Pb) <1000ppm

◎ 汞 (Hg) <1000ppm

◎ 六價鉻 (Cr6+) <1000ppm

◎ 多溴聯苯類 (PBB s) <1000ppm

◎ 多溴聯苯醚類 (PBDE s) <1000ppm

2.有鹵

DRAW NO. PGAS020734

GJS

PLASTIC TOLERANCE:

$L \leq 10$	± 0.2
$10 < L \leq 30$	± 0.3
$30 < L \leq 50$	± 0.5
$50 < L \leq 100$	± 0.7
$100 < L \leq 250$	± 1.2
ABOVE 250	± 1.5

網頁圖示供參考, 最終以品固公司正式圖面為主
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

MATERIAL: SANTOPRENE 251-70
or EQUIVALENT

PART NAME:

熱敏電阻座
NTC HOLDER

A

SIZE

VERSION

1B

COLOR: BLACK

PART NO:

HUC-02-RYB

SHEET 1 OF 1



UNIT	SCALE
mm	

試片硬度: 75°

表單號碼QF135