




◎ HOLE IN CHASSIS: $\phi 3.0^{+0.05}_0$ mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS035921 GJS

PLASTIC TOLERANCE: $L \leq 10 \pm 0.2$ $10 < L \leq 30 \pm 0.3$ $30 < L \leq 50 \pm 0.5$ $50 < L \leq 100 \pm 0.7$ $100 < L \leq 250 \pm 1.2$ ABOVE 250 ± 1.5	網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 鑽隆有限公司 <small>PINGOOD ENTERPRISE CO.,LTD.</small>	PART NAME: 散熱片鉚釘 MOUNTING BUTTON		VERSION A SIZE 2E
	MATERIAL: N66 V2 or EQUIVALENT COLOR: BLACK			PART NO: MB-15A-N2B		
	UNIT mm	SCALE 	SHEET 1 OF 1			