



◎ SUITABLE BUNDLE DIA: $\phi 30.0 \sim \phi 44.0$

- ◎ HOLE IN CHASSIS: $\phi 3.8$
- ◎ CHASSIS THICKNESS: $0.8 \sim 1.2$ mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS032113

GJS

PLASTIC TOLERANCE: $L \leq 5 \quad \pm 0.2$ $5 < L \leq 20 \quad \pm 0.3$ $20 < L \leq 40 \quad \pm 0.4$ $40 < L \leq 60 \quad \pm 0.5$ $50 < L \leq 100 \quad \pm 0.8$ ABOVE 100 ± 1.0		網頁圖示供參考,最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 PINGOOD ENTERPRISE CO.,LTD.		PART NAME: 電源收線固定帶 STRAP TIE		VERSION A 1	
MATERIAL: PE or EQUIVALENT COLOR: BLACK		PART NO.: BST-172CF-PEB				SHEET 1 OF 1			
 UNIT mm		SCALE 