



- ◎ HOLE IN CHASSIS: $\phi 3.2$
- ◎ CHASSIS THICKNESS: 1.6 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS033001 GJS

| | | |
|---------------------------|------|---|
| PLASTIC TOLERANCE: | | 網頁圖示供參考,最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD. |
| L≤10 | ±0.2 | |
| 10<L≤30 | ±0.3 | |
| 30<L≤50 | ±0.5 | |
| 50<L≤100 | ±0.7 | |
| 100<L≤250 | ±1.2 | |
| ABOVE 250 | ±1.5 | |

MATERIAL: N66 V2 or EQUIVALENT

COLOR: NATURAL



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
東莞市鑽隆商貿有限公司
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:

隔離束線座
WIRE SADDLE

A

VERSION

SIZE

1

PART NO:

CBG-6PK-N2W

SHEET 1 OF 1

| | | |
|--|------|-------|
| | UNIT | SCALE |
| | mm | |