




◎ HOLE IN CHASSIS:



◎ CHASSIS THICKNESS: $1.0^{+0}_{-0.05}$ mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS036533 GJS

PLASTIC TOLERANCE: $L \leq 10 \pm 0.2$ $10 < L \leq 30 \pm 0.3$ $30 < L \leq 50 \pm 0.5$ $50 < L \leq 100 \pm 0.7$ $100 < L \leq 250 \pm 1.2$ ABOVE 250 ± 1.5		網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鈺隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD.		PART NAME: 印刷電路板導槽 PCB GUIDE RAIL		VERSION A 1A	
MATERIAL: N66 V2 or EQUIVALENT COLOR: NATURAL		PART NO.: CG-56FY-N2W				SHEET 1 OF 1			
 UNIT SCALE mm		SHEET 1 OF 1							