




◎ 高度不含離形紙厚度

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS036669 GJS

<b>PLASTIC TOLERANCE:</b> $L \leq 10 \pm 0.2$ $10 < L \leq 30 \pm 0.3$ $30 < L \leq 50 \pm 0.5$ $50 < L \leq 100 \pm 0.7$ $100 < L \leq 250 \pm 1.2$ ABOVE 250 $\pm 1.5$	網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD.	<b>PART NAME:</b> 隔離束線座 WIRE SADDLE		<b>VERSION</b> A 1	
	<b>MATERIAL:</b> N66 V2 or EQUIVALENT			<b>PART NO.:</b> CKZ-16-NQW			
	<b>COLOR:</b> NATURAL			<b>THICKNESS OF ADHESIVE TAPE:</b> $0.8^{+0.45}_{-0.15}$ mm		<b>SHEET 1 OF 1</b>	
	<b>ADHESIVE TAPE:</b> 3M (1600T) or EQUIVALENT						
	<b>UNIT</b> mm	<b>SCALE</b> 					

表單號碼 QF135