

 \odot HOLE IN CHASSIS: $\emptyset 4.3^{+0.05}_{-0}$ mm \odot CHASSIS THICKNESS: $5.0^{+0}_{-0.05}$ mm

◎Halogen Free 低鹵 ◎ROHS 2.0 ◎ROHS 六項 compliant					t
			DRAW NO. PGAS036	525	GJS
PLASTIC TOLERANCE: $L \le 10$ ± 0.2 $10 < L \le 30$ ± 0.3 $30 < L \le 50$ ± 0.5	網頁圖示供參考,最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.	P	品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市钻陸商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.LTD.		
50 <l≤100 ±0.7<br="">100<l≤250 td="" ±1.2<=""><td>MATERIAL: N66 V2 or EQUIVALENT COLOR: BLACK</td><td>PART NAME: 障</td><td>離束線座</td><td>A</td><td>VERSION</td></l≤250></l≤100>	MATERIAL: N66 V2 or EQUIVALENT COLOR: BLACK	PART NAME: 障	離束線座	A	VERSION
ABOVE 250 ± 1.5			IRE SADDLE	SIZE	. 2
			/F—24GH—N2B	SHEET	1 OF 1
				表單號	 痣QF135