



◎ 高度不含離形紙厚度

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS037092 GJS

<b>PLASTIC TOLERANCE:</b> $L \leq 10 \quad \pm 0.2$ $10 < L \leq 30 \quad \pm 0.3$ $30 < L \leq 50 \quad \pm 0.5$ $50 < L \leq 100 \quad \pm 0.7$ $100 < L \leq 250 \quad \pm 1.2$ ABOVE 250 $\pm 1.5$		網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.
<b>MATERIAL:</b> N66 V2 or EQUIVALENT <b>COLOR:</b> BLACK <b>ADHESIVE TAPE:</b> 3M (1600T) or EQUIVALENT <b>THICKNESS OF ADHESIVE TAPE:</b> $0.8^{+0.45}_{-0.15}$ mm		
	UNIT mm	SCALE 



品固企業股份有限公司  
 品基電子(東莞)有限公司  
 蘇州品基電子科技有限公司  
 東莞市鑽隆商貿有限公司  
 鑽隆有限公司  
 PINGOOD ENTERPRISE CO.,LTD.

<b>PART NAME:</b> 電線固定板 CABLE CLAMP		<b>VERSION</b> A <b>SIZE</b> 1
<b>PART NO.:</b> FCW-40GQ-NQB		
<b>SHEET 1 OF 1</b>		

表單號碼QF135