

◎ 高度不含離形紙厚度

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS034929

GJS

| | |
|---------------------------|------|
| PLASTIC TOLERANCE: | |
| L ≤ 10 | ±0.2 |
| 10 < L ≤ 30 | ±0.3 |
| 30 < L ≤ 50 | ±0.5 |
| 50 < L ≤ 100 | ±0.7 |
| 100 < L ≤ 250 | ±1.2 |
| ABOVE 250 | ±1.5 |

網頁圖示供參考,最終以品固公司正式圖面為主
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
東莞市鑽隆商貿有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

MATERIAL: N66 V2 or EQUIVALENT

PART NAME:

P.C. 板間隔柱
SPACER SUPPORT

A
SIZE

VERSION
1


ADHESIVE TAPE: 3M (1600T) or EQUIVALENT

PART NO.:

FKM-27JC-NQW

SHEET 1 OF 1

THICKNESS OF ADHESIVE TAPE : 0.8^{+0.45}_{-0.15}mm



| | |
|------|-------|
| UNIT | SCALE |
| mm | |