

◎ HOLE IN CHASSIS:

◎ CHASSIS THICKNESS: $1.4^{+0}_{-0.05}$ mm

◎ROHS 六項 compliant

鎘(Cd) < 100ppm

鉛(Pb) < 1000ppm

汞(Hg) < 1000ppm

六價鉻(Cr^{+6}) < 1000ppm

多溴聯苯總和(PBBs) < 1000ppm

多溴聯苯醚總和(PBDEs) < 1000ppm

◎Halogen 有鹵

DRAW NO. PGAS036351

GJS

PLASTIC TOLERANCE:

$L \leq 10 \pm 0.2$

$10 < L \leq 30 \pm 0.3$

$30 < L \leq 50 \pm 0.5$

$50 < L \leq 100 \pm 0.7$

$100 < L \leq 250 \pm 1.2$

ABOVE 250 ± 1.5

網頁圖示供參考, 最終以品固公司正式圖面為主

The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: SANTOPRENE V0 251-70
or EQUIVALENT

COLOR: BLACK

試片硬度: 75°



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
東莞市品基商貿有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:

防震華司
SHOCK-ABSORB WASHER

PART NO:


GSD-01-RYB

A
SIZE

VERSION

1C

SHEET 1 OF 1



UNIT SCALE
mm

表單號碼QF135