



- ◎ P.C.B THICKNESS: 1.8~2.0 mm
- ◎ HOLE IN DIMENSIONS:  $\phi 4.0$

◎ROHS compliant

DRAW NO. PGAS012063 E GJS

|                                       |  |
|---------------------------------------|--|
| <b>PLASTIC TOLERANCE:</b>             | 網頁圖示供參考, 最終以品固公司正式圖面為主   |
| L ≤ 10 ±0.2                           | The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD. |
| 10 < L ≤ 30 ±0.3                      |  |
| 30 < L ≤ 50 ±0.5                      |  |
| 50 < L ≤ 100 ±0.7                     |  |
| 100 < L ≤ 250 ±1.2                    |  |
| ABOVE 250 ±1.5                        |  |
| <b>MATERIAL:</b> N66 V2 or EQUIVALENT |  |
| <b>COLOR:</b> BLACK                   |  |



品固企業股份有限公司  
品基電子(東莞)有限公司  
蘇州品基電子科技有限公司  
鑽隆有限公司  
PINGOOD ENTERPRISE CO.,LTD.

**PART NAME:**  
P.C. 板間隔柱  
SPACER SUPPORT

|           |      |
|-----------|------|
| A<br>SIZE | REV. |
|           | 1    |

**PART NO:**  
LCD-151N2B

SHEET 1 OF 1

|  |      |       |
|--|------|-------|
|  | UNIT | SCALE |
|  | mm   |       |