



- ◎ HOLE IN CHASSIS:  $\phi 4.0$
- ◎ MAXIMUM THICKNESS: 2.0 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS024165 GJS

<b>PLASTIC TOLERANCE:</b>			網頁圖示供參考,最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.				
L≤10	±0.2						
10<L≤30	±0.3						
30<L≤50	±0.5						
50<L≤100	±0.7						
100<L≤250	±1.2						
ABOVE 250	±1.5						
<table border="1"> <tr> <td>UNIT</td> <td>SCALE</td> </tr> <tr> <td>mm</td> <td></td> </tr> </table>			UNIT	SCALE	mm		
UNIT	SCALE						
mm							



品固企業股份有限公司  
 品基電子(東莞)有限公司  
 蘇州品基電子科技有限公司  
 鑽隆有限公司  
 PINGOOD ENTERPRISE CO.,LTD.

MATERIAL: N66 V2 or EQUIVALENT		PART NAME: <b>P.C. 板間隔柱</b> SPACER SUPPORT	VERSION <b>A</b>
COLOR: NATURAL			
PART NO: LLS-12-N2W		SIZE <b>A</b>	VERSION <b>3A</b>
		SHEET 1 OF 1	