



◎ HOLE IN P.C.B.:

◎ P.C.B. THICKNESS:  $1.6^{+0}_{-0.05}$  mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS036621

GJS

**PLASTIC TOLERANCE:**

|                    |           |
|--------------------|-----------|
| $L \leq 10$        | $\pm 0.2$ |
| $10 < L \leq 30$   | $\pm 0.3$ |
| $30 < L \leq 50$   | $\pm 0.5$ |
| $50 < L \leq 100$  | $\pm 0.7$ |
| $100 < L \leq 250$ | $\pm 1.2$ |
| ABOVE 250          | $\pm 1.5$ |

網頁圖示供參考, 最終以品固公司正式圖面為主

The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

**MATERIAL:** N66 V2 or EQUIVALENT

**COLOR:** NATURAL



品固企業股份有限公司  
品基電子(東莞)有限公司  
蘇州品基電子科技有限公司  
東莞市鑽隆商貿有限公司  
鑽隆有限公司  
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:

**P.C. 板間隔柱  
SPACER SUPPORT**

**A**

SIZE

VERSION

1

PART NO:

LTX-13-N2W

SHEET 1 OF 1

|  |      |       |
|--|------|-------|
|  | UNIT | SCALE |
|  | mm   |       |

表單號碼 QF135