



© CHASSIS THICKNESS: >2.6 mm ◎ HOLE IN CHASSIS: Ø1.8

| ◎Halogen Free 低鹵 ◎ROHS 2.0 ◎ROHS 六項 compliant | | | | | ant |
|---|---|------------------|----------------------------|-------|---------|
| | | | DRAW NO. PGAS023 | | GJS |
| PLASTIC TOLERANCE: | 網頁圖示供參考,最終以品固公司正式圖面為主 | \bigcirc | 品固企業股份有 | | _ |
| L≤10 ±0.2 | The plastic tolerance is just for your reference; all | 」 し に う | 品基電子(東莞 | | |
| 10 <l≤30 td="" ±0.3<=""><td>the measurements and dimensions are according</td><td></td><td>蘇州品基電子和</td><td></td><td>公司</td></l≤30> | the measurements and dimensions are according | | 蘇州品基電子和 | | 公司 |
| 30 <l≤50 td="" ±0.5<=""><td>to the "DATA SHEET" issued by PINGOOD.</td><td></td><td>鑽隆有限公 PINGOOD ENTERPRIS</td><td></td><td></td></l≤50> | to the "DATA SHEET" issued by PINGOOD. | | 鑽隆有限公 PINGOOD ENTERPRIS | | |
| 50 <l≤100 td="" ±0.7<=""><td>MATERIAL: N66 VO or EQUIVALENT</td><td>PART NAME:</td><td></td><td>Δ</td><td>VERSION</td></l≤100> | MATERIAL: N66 VO or EQUIVALENT | PART NAME: | | Δ | VERSION |
| 100 <l≤250 td="" ±1.2<=""><td></td><td>釦</td><td>釘</td><td></td><td>VENSION</td></l≤250> | | 釦 | 釘 | | VENSION |
| ABOVE 250 ±1.5 | COLOR: NATURAL | CANOE | - • | | 2A |
| UNIT SCALE | - | PART NO: | ULIF | SIZE | 2/1 |
| | - | | 4C-NOW | SHEET | 1 OF 1 |
| 表單號碼QF135 | | | | | |