


音源孔適用:

- © HOLE IN CHASSIS: Ø3.5~Ø3.7
- © CHASSIS THICKNESS: >8.8 mm

鉚釘適用:

- © HOLE IN CHASSIS: Ø3.6~Ø3.65
- © CHASSIS THICKNESS: 2.4~2.6 mm



- ⊚Halogen Free 低鹵
- ◎ROHS 2.0 ◎ROHS 六項 compliant

		DRAW NO. PGASO3.	5045	GJS
PLASTIC TOLERANCE: $L \le 10$ ± 0.2 $10 < L \le 30$ ± 0.3 $30 < L \le 50$ ± 0.5	網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.	品固企業股份 品基電子(東 蘇州品基電子 東莞市钻隆 衛隆有限公司 PINGOOD ENTERF	莞)有限公司 一科技有限公司 可貿有限公司]	一司
50 <l≤100 ±0.7<br="">100<l≤250 td="" ±1.2<=""><td>MATERIAL: N66 V2 or EQUIVALENT</td><td>PART NAME:</td><td>A</td><td>VERSION</td></l≤250></l≤100>	MATERIAL: N66 V2 or EQUIVALENT	PART NAME:	A	VERSION
ABOVE 250 ±1.5	COLOR: NATURAL	鉚釘 - CANOE CLIP	SIZE	1A
WNIT SCALE mm		PART NO: MBJ—3A—N2W	SHEET	1 OF 1