



◎ HOLE IN P.C.B.:  $\phi 4.0$

◎ P.C.B. THICKNESS: 0.6~0.8 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS030510

GJS

|                                       |      |  |
|---------------------------------------|------|--|
| <b>PLASTIC TOLERANCE:</b>             |      | 網頁圖示供參考, 最終以品固公司正式圖面為主   |
| L ≤ 10                                | ±0.2 | The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD. |
| 10 < L ≤ 30                           | ±0.3 |  |
| 30 < L ≤ 50                           | ±0.5 |  |
| 50 < L ≤ 100                          | ±0.7 |  |
| 100 < L ≤ 250                         | ±1.2 |  |
| ABOVE 250                             | ±1.5 |  |
| <b>MATERIAL:</b> N66 V2 or EQUIVALENT |      |  |
| <b>COLOR:</b> NATURAL                 |      |  |



品固企業股份有限公司  
品基電子(東莞)有限公司  
蘇州品基電子科技有限公司  
東莞市鑽隆商貿有限公司  
PINGOOD ENTERPRISE CO.,LTD.

**PART NAME:**  
P.C. 板間隔柱  
SPACER SUPPORT

|          |         |
|----------|---------|
| <b>A</b> | VERSION |
|          | 1       |
| SIZE     |         |

**PART NO:**  
MC-1AK-N2W

SHEET 1 OF 1

|  |      |       |
|--|------|-------|
|  | UNIT | SCALE |
|  | mm   |       |