



◎ HOLE IN P.C.B.: $\phi 2.5 \pm_{-0}^{+0.05}$ mm

◎ P.C.B. THICKNESS: $0.5 \pm_{-0.05}^{+0}$ mm



◎ HOLE IN P.C.B.: $\phi 3.0 \pm_{-0}^{+0.05}$ mm

◎ P.C.B. THICKNESS: $0.8 \pm_{-0.05}^{+0}$ mm

◎Halogen Free 低鹵

◎RoHS Compliant

DRAW NO. PGAS046093

GJS

PLASTIC TOLERANCE:

$L \leq 10 \pm 0.2$

$10 < L \leq 30 \pm 0.3$

$30 < L \leq 50 \pm 0.5$

$50 < L \leq 100 \pm 0.7$

$100 < L \leq 250 \pm 1.2$

ABOVE 250 ± 1.5

網頁圖示供參考,最終以品固公司正式圖面為主

The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: PA66(N66) V2 or EQUIVALENT

COLOR: NATURAL



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
東莞市品基商貿有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:


P.C. 板間隔柱
SPACER SUPPORT

PART NO:

MEG-04A-N2W

A
SIZE

VERSION



UNIT
mm

SCALE