



- ◎ HOLE IN P.C.B. :  $\phi 5.9\text{mm}$
- ◎ P.C.B THICKNESS: 4.5 mm
- ◎ 所有尺寸量測皆不含進澆口, 澆口凸出0.1mm 之內

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS022216 GJS

|                    |           |
|--------------------|-----------|
| PLASTIC TOLERANCE: |           |
| $L \leq 10$        | $\pm 0.2$ |
| $10 < L \leq 30$   | $\pm 0.3$ |
| $30 < L \leq 50$   | $\pm 0.5$ |
| $50 < L \leq 100$  | $\pm 0.7$ |
| $100 < L \leq 250$ | $\pm 1.2$ |
| ABOVE 250          | $\pm 1.5$ |

網頁圖示供參考, 最終以品固公司正式圖面為主  
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.



品固企業股份有限公司  
品基電子(東莞)有限公司  
蘇州品基電子科技有限公司  
鑽隆有限公司  
PINGOOD ENTERPRISE CO.,LTD.

MATERIAL: N66 V2 or EQUIVALENT

PART NAME:

鉚釘  
SNAP RIVET

|           |         |
|-----------|---------|
| A<br>SIZE | VERSION |
|           | 1       |

COLOR: BLACK

PART NO:

MEL-6A-N2B-Z

SHEET 1 OF 1

|  |      |       |
|--|------|-------|
|  | UNIT | SCALE |
|  | mm   |       |