



SECTION A-A

- ◎ HOLE IN CHASSIS: $\phi 5.0$
- ◎ CHASSIS THICKNESS: 3.4 mm

- ◎HF
- ◎ROHS compliant

DRAW NO. PGAS016808 GJS

| PLASTIC TOLERANCE: | |
|--------------------|-----------|
| $L \leq 10$ | ± 0.2 |
| $10 < L \leq 30$ | ± 0.3 |
| $30 < L \leq 50$ | ± 0.5 |
| $50 < L \leq 100$ | ± 0.7 |
| $100 < L \leq 250$ | ± 1.2 |
| ABOVE 250 | ± 1.5 |

網頁圖示供參考,最終以品固公司正式圖面為主
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: N66 V2 or EQUIVALENT
COLOR: NATURAL



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:
板間隔柱
SPACER SUPPORT

PART NO:
MHT-05-N2W

| | |
|------|---------|
| A | VERSION |
| | 1 |
| SIZE | |

SHEET 1 OF 1

| | | |
|--|------|-------|
| | UNIT | SCALE |
| | mm | |