

◎Halogen Free 低鹵 ◎ROHS 2.0 ◎ROHS 六項 compliant

DRAW NO. PGASO29560

		DRAW NO. PGASU29	560	605
PLASTIC TOLERANCE:	網頁圖示供參考, 最終以品固公司正式圖面為主	○ 品固企業股份	有限公司	司
L≤10 ±0.2	The plastic tolerance is just for your reference; all	【○【○【○】 品基電子(東	莞)有限公	公司
10 <l≤30 td="" ±0.3<=""><td>the measurements and dimensions are according</td><td>蘇州品基電子</td><td></td><td></td></l≤30>	the measurements and dimensions are according	蘇州品基電子		
30 <l≤50 td="" ±0.5<=""><td>to the "DATA SHEET" issued by PINGOOD.</td><td>東莞市鑚隆商 PINGOOD ENTER!</td><td></td><td></td></l≤50>	to the "DATA SHEET" issued by PINGOOD.	東莞市鑚隆商 PINGOOD ENTER!		
50 <l≤100 td="" ±0.7<=""><td>MATERIAL: N66 V2 or EQUIVALENT</td><td>PART NAME:</td><td>enterval enterval</td><td>VERSION</td></l≤100>	MATERIAL: N66 V2 or EQUIVALENT	PART NAME:	enterval enterval	VERSION
100 <l≤250 td="" ±1.2<=""><td>WATERIAL. 1100 VZ OF EQUIVALENT</td><td>P. C. 板間隔柱</td><td>/\\</td><td>VENSION</td></l≤250>	WATERIAL. 1100 VZ OF EQUIVALENT	P. C. 板間隔柱	/\\	VENSION
ABOVE 250 ±1.5	COLOR: NATURAL	, <u> </u>		1
ABOVE 230 II.3		SPACER SUPPORT	SIZE	/
UNIT SCALE		PART NO:	O,ZL	
mm SOALL]	<i>MQF-14DC-N2W</i>	SHEET	1 OF 1