



- ◎ HOLE IN P.C.B.: $\phi 4.0^{+0.05}_0$ mm
- ◎ P.C.B. THICKNESS: $1.0^{+0}_{-0.05}$ mm
- ◎ 高度不含離形紙厚度

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS037073

GJS

PLASTIC TOLERANCE: $L \leq 10$ ± 0.2 $10 < L \leq 30$ ± 0.3 $30 < L \leq 50$ ± 0.5 $50 < L \leq 100$ ± 0.7 $100 < L \leq 250$ ± 1.2 ABOVE 250 ± 1.5		網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD.	PART NAME: P.C. 板間隔柱 SPACER SUPPORT		VERSION A 1
MATERIAL: N66 V2 or EQUIVALENT COLOR: NATURAL ADHESIVE TAPE: 3M (1600T) or EQUIVALENT		THICKNESS OF ADHESIVE TAPE: $0.8^{+0.15}_{-0.13}$ mm			PART NO.: MSY-2A-NQW		
 UNIT mm SCALE							