





◎ CHASSIS THICKNESS: $0.8^{+0}_{-0.05}$ mm



◎ HOLE IN P.C.B.:



◎ P.C.B. THICKNESS: $1.6^{+0}_{-0.05}$ mm

◎ Halogen Free 低鹵
◎ ROHS 2.0
◎ ROHS 六項 compliant

DRAW NO. PGAS038978

GJS

PLASTIC TOLERANCE:

$L \leq 10$	± 0.2
$10 < L \leq 30$	± 0.3
$30 < L \leq 50$	± 0.5
$50 < L \leq 100$	± 0.7
$100 < L \leq 250$	± 1.2
ABOVE 250	± 1.5

網頁圖示供參考,最終以品固公司正式圖面為主

The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: N66 V0 or EQUIVALENT

COLOR: BLACK



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
東莞市鑽隆商貿有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:


固定座
MOUNT

A
SIZE

VERSION

PART NO:

MTQ-2A-U0B



UNIT
mm

SCALE