



- ◎ SUITABLE BUNDLE DIA: $\phi 5.0 \sim \phi 6.5$
- ◎ HOLE IN CHASSIS: $\phi 6.4 \sim \phi 6.5$
- ◎ CHASSIS THICKNESS: 0.8~2.4 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS027442 GJS

PLASTIC TOLERANCE: L ≤ 10 ±0.2 10 < L ≤ 30 ±0.3 30 < L ≤ 50 ±0.5 50 < L ≤ 100 ±0.7 100 < L ≤ 250 ±1.2 ABOVE 250 ±1.5		網頁圖示供參考,最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 PINGOOD ENTERPRISE CO.,LTD.	
MATERIAL: N66 V2 or EQUIVALENT COLOR: NATURAL		PART NAME: 電線固定座 WIRE MOUNT			
 UNIT mm		SCALE		PART NO: PDT-06-N2W	
				SHEET 1 OF 1	