

OPEN

樣品裝置於 $\phi 22.0$ 裝配孔量測

CLOSE

◎ HOLE IN DIMENSIONS: $\phi 22.0$

◎ CHASSIS THICKNESS: 0.8~1.2 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS033620

GJS

PLASTIC TOLERANCE:	
$L \leq 10$	± 0.2
$10 < L \leq 30$	± 0.3
$30 < L \leq 50$	± 0.5
$50 < L \leq 100$	± 0.7
$100 < L \leq 250$	± 1.2
ABOVE 250	± 1.5

網頁圖示供參考,最終以品固公司正式圖面為主
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: N66 V2 or EQUIVALENT

COLOR: BLACK



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
東莞市鑽隆商貿有限公司
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:

開口式護線環
OPEN CLOSED BUSHING

A
SIZE


VERSION

2B

PART NO:

SB-1922A

SHEET 1 OF 1



UNIT	SCALE
mm	