




- ◎ HOLE IN CHASSIS: $\phi 1.5^{+0.05}_0$ mm
- ◎ CHASSIS THICKNESS: 2.0~2.5 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS036523 GJS

PLASTIC TOLERANCE: $L \leq 10$ ± 0.2 $10 < L \leq 30$ ± 0.3 $30 < L \leq 50$ ± 0.5 $50 < L \leq 100$ ± 0.7 $100 < L \leq 250$ ± 1.2 ABOVE 250 ± 1.5		網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD.	
MATERIAL: N66 V2 or EQUIVALENT COLOR: BLACK		PART NAME: 尼龍鉚釘 SNAP RIVET			
 UNIT mm		SCALE 		PART NO.: SR-1FM-N2B-Z	
SHEET 1 OF 1 表單號碼QF135					