

 $\bigcirc$  HOLE IN CHASSIS:  $\emptyset 2.0^{+0.05}_{-0}$  mm

© CHASSIS THICKNESS: 2.5~3.5 mm

⊚Halogen Free 低鹵

◎ROHS 2.0 ◎ROHS 六項 compliant

DRAW NO. PGAS038366 GJS

PLASTIC TOLERANCE: 網頁圖示供參考, 最終以品固公司正式圖面為主  $\pm 0.2$ L≤10 The plastic tolerance is just for your reference; all 10<L≤30  $\pm 0.3$ the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD. 30<L≤50  $\pm 0.5$ 50<L≤100 ±0.7 MATERIAL: N66 V2 or EQUIVALENT 100<L≤250 ±1.2 COLOR: BLACK ABOVE 250 ±1.5 UNIT SCALE

mm

PG

品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市钻隆商貿有限公司 鑽隆有限公司

興性力 IN A り PINGOOD ENTERPRISE CI

PART NAME:

尼龍鉚釘 SNAP RIVET A

VERSION 1

PART NO: SR-2FR-N2B-X

SHEET 1 OF 1

表單號碼QF135