




- ◎ HOLE IN P.C.B.: $\phi 2.5 \pm_{0}^{0.05}$ mm
- ◎ P.C.B. THICKNESS: 0.5~1.0 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS038222 GJS

| | | | | | |
|---|--|--|--|---|--|
| PLASTIC TOLERANCE: L ≤ 10 ±0.2 10 < L ≤ 30 ±0.3 30 < L ≤ 50 ±0.5 50 < L ≤ 100 ±0.7 100 < L ≤ 250 ±1.2 ABOVE 250 ±1.5 | | 網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD. | |  品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市崑隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD. | |
| MATERIAL: N66 V2 or EQUIVALENT COLOR: BLACK | | PART NAME: 尼龍鉚釘 SNAP RIVET | | | |
|  UNIT mm | | SCALE  | | PART NO.: SR-2GQ-N2B-Z | |
| SHEET 1 OF 1 表單號碼 QF135 | | | | | |