



◎ HOLE IN CHASSIS:  $\phi 2.1$

◎ CHASSIS THICKNESS: 2.8~3.6 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS023058

GJS

|                    |      |
|--------------------|------|
| PLASTIC TOLERANCE: |      |
| L ≤ 10             | ±0.2 |
| 10 < L ≤ 30        | ±0.3 |
| 30 < L ≤ 50        | ±0.5 |
| 50 < L ≤ 100       | ±0.7 |
| 100 < L ≤ 250      | ±1.2 |
| ABOVE 250          | ±1.5 |

網頁圖示供參考, 最終以品固公司正式圖面為主  
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.



品固企業股份有限公司  
品基電子(東莞)有限公司  
蘇州品基電子科技有限公司  
鑽隆有限公司  
PINGOOD ENTERPRISE CO.,LTD.

MATERIAL: N66 V2 or EQUIVALENT

PART NAME:

尼龍鉚釘  
SNAP RIVET

A

SIZE

VERSION

1A

COLOR: BLACK

PART NO.:

SR-2J-Z

SHEET 1 OF 1



UNIT  
mm

SCALE