



PLASTIC TOLERANCE:

- ◎ HOLE IN P.C.B.:  $\phi 2.5 \pm_{-0}^{0.05}$  mm
- ◎ P.C.B. THICKNESS: 2.0~3.0 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS037342 GJS

PLASTIC TOLERANCE: $L \leq 10 \quad \pm 0.2$ $10 < L \leq 30 \quad \pm 0.3$ $30 < L \leq 50 \quad \pm 0.5$ $50 < L \leq 100 \quad \pm 0.7$ $100 < L \leq 250 \quad \pm 1.2$ ABOVE 250 $\pm 1.5$		網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD.			
MATERIAL: N66 V2 or EQUIVALENT COLOR: BLACK		PART NAME: <b>尼龍鉚釘</b> SNAP RIVET				VERSION <b>A</b> SIZE 1	
UNIT mm		SCALE 		PART NO: SR-2JB-N2B-X		SHEET 1 OF 1	