



◎ HOLE IN P.C.B.: $\phi 2.5^{+0.05}_{-0}$ mm
 ◎ P.C.B. THICKNESS: 2.5~3.5 mm

◎ Halogen Free 低鹵
 ◎ ROHS 2.0
 ◎ ROHS 六項 compliant

DRAW NO. PGAS038351 GJS

PLASTIC TOLERANCE: $L \leq 10$ ±0.2 $10 < L \leq 30$ ±0.3 $30 < L \leq 50$ ±0.5 $50 < L \leq 100$ ±0.7 $100 < L \leq 250$ ±1.2 ABOVE 250 ±1.5	網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.	 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市崑隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD.	PART NAME: 尼龍鉚釘 SNAP RIVET		VERSION A 1A
	MATERIAL: N66 V2 or EQUIVALENT COLOR: BLACK		PART NO.: SR-2KY-N2B-X		
 UNIT SCALE mm					