



◎ HOLE IN P.C.B.: $\phi 3.5^{+0.05}_0$ mm

◎ P.C.B. THICKNESS: 1.6~2.2 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS036411

GJS

| | |
|--------------------|-----------|
| PLASTIC TOLERANCE: | |
| $L \leq 10$ | ± 0.2 |
| $10 < L \leq 30$ | ± 0.3 |
| $30 < L \leq 50$ | ± 0.5 |
| $50 < L \leq 100$ | ± 0.7 |
| $100 < L \leq 250$ | ± 1.2 |
| ABOVE 250 | ± 1.5 |

網頁圖示供參考, 最終以品固公司正式圖面為主
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: N66 V2 or EQUIVALENT

COLOR: BLACK



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
東莞市鑽隆商貿有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:

P.C. 板固定扣
P.C.B. RIVET

PART NO.:

SRTK-3GP-N2B

A

SIZE

VERSION

1

SHEET 1 OF 1

| | | |
|--|------|-------|
| | UNIT | SCALE |
| | mm | |

表單號碼 QF135