

4.1

○ HOLE IN CHASSIS: Ø4.8~Ø5.0

© CHASSIS THICKNESS: 0.5~2.1 mm

⊚Halogen Free 低鹵

◎ROHS 2.0

◎ROHS 六項 compliant

DRAW NO. PGASO23151

GJS

 $\begin{array}{cccc} & \text{PLASTIC TOLERANCE:} \\ & & \text{L} \leq 10 & \pm 0.2 \\ & 10 < \text{L} \leq 30 & \pm 0.3 \\ & 30 < \text{L} \leq 50 & \pm 0.5 \\ & 50 < \text{L} \leq 100 & \pm 0.7 \\ & 100 < \text{L} \leq 250 & \pm 1.2 \\ & \text{ABOVE 250} & \pm 1.5 \\ \end{array}$

網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: N66 V2 or EQUIVALENT
COLOR: NATURAL

PG

品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 鑽 隆 有 限 公 司 PINGOOD ENTERPRISE CO.,LTD.

PART NAME:

隔離束線座 WIRE SADDLE

SIZE

VERSION 1 A

UNIT SCALE

PART NO:

TUA-34-N2W

SHEET 1 OF 1