



- ◎ HOLE IN CHASSIS: $\phi 4.5$
- ◎ CHASSIS THICKNESS: 1.6 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS023916 GJS

| PLASTIC TOLERANCE: | |
|--------------------|------|
| L ≤ 10 | ±0.2 |
| 10 < L ≤ 30 | ±0.3 |
| 30 < L ≤ 50 | ±0.5 |
| 50 < L ≤ 100 | ±0.7 |
| 100 < L ≤ 250 | ±1.2 |
| ABOVE 250 | ±1.5 |

網頁圖示供參考，最終以品固公司正式圖面為主
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.



品固企業股份有限公司
品基電子(東莞)有限公司
蘇州品基電子科技有限公司
鑽隆有限公司
PINGOOD ENTERPRISE CO.,LTD.

MATERIAL: N66 V2 or EQUIVALENT
COLOR: NATURAL

PART NAME:
隔離束線座
WIRE SADDLE

| | |
|-----------|---------|
| A SIZE | VERSION |
| | 2A |

PART NO:
TUA-40-N2W

SHEET 1 OF 1

| UNIT | SCALE |
|------|-------|
| mm | |