


◎ HOLE IN CHASSIS:



◎ MAXIMUM THICKNESS: 1.6 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS023565 GJS

|                           |      |
|---------------------------|------|
| <b>PLASTIC TOLERANCE:</b> |      |
| L ≤ 10                    | ±0.2 |
| 10 < L ≤ 30               | ±0.3 |
| 30 < L ≤ 50               | ±0.5 |
| 50 < L ≤ 100              | ±0.7 |
| 100 < L ≤ 250             | ±1.2 |
| ABOVE 250                 | ±1.5 |

網頁圖示供參考, 最終以品固公司正式圖面為主  
The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.

MATERIAL: N66 V2 or EQUIVALENT  
COLOR: NATURAL



品固企業股份有限公司  
品基電子(東莞)有限公司  
蘇州品基電子科技有限公司  
鑽隆有限公司  
PINGOOD ENTERPRISE CO.,LTD.

PART NAME:  
P.C. 板間隔柱  
SPACER SUPPORT

|      |         |
|------|---------|
| A    | VERSION |
|      | 4A      |
| SIZE |         |

PART NO:  
UB-05A-N2W

SHEET 1 OF 1

|  |      |       |
|--|------|-------|
|  | UNIT | SCALE |
|  | mm   |       |