



- ◎ HOLE IN CHASSIS:  $\phi 3.3$
- ◎ MAXIMUM THICKNESS: 1.6 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS023928 GJS

|   |  |                   |  |  |              |                                |
|---|--|-------------------|--|--|--------------|--------------------------------|
| <b>PLASTIC TOLERANCE:</b><br>L ≤ 10 ± 0.2<br>10 < L ≤ 30 ± 0.3<br>30 < L ≤ 50 ± 0.5<br>50 < L ≤ 100 ± 0.7<br>100 < L ≤ 250 ± 1.2<br>ABOVE 250 ± 1.5 | 網頁圖示供參考, 最終以品固公司正式圖面為主<br>The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD. |                   |  品固企業股份有限公司<br>品基電子(東莞)有限公司<br>蘇州品基電子科技有限公司<br>鑽隆有限公司<br>PINGOOD ENTERPRISE CO.,LTD. | <b>PART NAME:</b><br>P.C. 板間隔柱<br>SPACER SUPPORT |              | <b>VERSION</b><br>A<br>SIZE 2A |
|   | <b>MATERIAL:</b> N66 V2 or EQUIVALENT<br><b>COLOR:</b> NATURAL   |                   |  | <b>PART NO.:</b><br>UB-7                         |              |                                |
|   |    | <b>UNIT</b><br>mm |  | <b>SCALE</b><br>                                 | SHEET 1 OF 1 |                                |