



◎ HOLE IN CHASSIS:  $\phi 6.5^{+0.05}_0$  mm

◎ CHASSIS THICKNESS: 0.8~1.8 mm

- ◎ Halogen Free 低鹵
- ◎ ROHS 2.0
- ◎ ROHS 六項 compliant

DRAW NO. PGAS029902 GJS

PLASTIC TOLERANCE: $L \leq 10 \pm 0.2$ $10 < L \leq 30 \pm 0.3$ $30 < L \leq 50 \pm 0.5$ $50 < L \leq 100 \pm 0.7$ $100 < L \leq 250 \pm 1.2$ ABOVE 250 $\pm 1.5$		網頁圖示供參考, 最終以品固公司正式圖面為主 The plastic tolerance is just for your reference; all the measurements and dimensions are according to the "DATA SHEET" issued by PINGOOD.		 品固企業股份有限公司 品基電子(東莞)有限公司 蘇州品基電子科技有限公司 東莞市鑽隆商貿有限公司 鑽隆有限公司 PINGOOD ENTERPRISE CO.,LTD.	PART NAME: <b>電線束線帶</b> MOUNTING CABLE TIE		A SIZE	VERSION 3
MATERIAL: N66 V2 or EQUIVALENT COLOR: NATURAL		PART NO: YAA-118N2W			SHEET 1 OF 1			
	UNIT mm	SCALE 						